


Thermal Memory Ltd

6 Dodd Croft
Rochdale
Lancashire OL16 4QX
Great Britain

Website : www.shrinkfit.co.uk E-mail : shrinkfit@gmail.com

MW PTFE is extremely stable at high temperatures & can be used continuously at **+260°C**

It is one of the few polymers that retains a measure of toughness and strength even at cryogenic temperatures & has been used safely in outer space at temperatures well below **-70°C**. It is virtually inert to all chemicals, organic solvents do not attack or dissolve it and is extremely hydrophobic and sheds vapours almost totally.



MW Teflon Metric Wall tubing.

Metric wall ID 1.0 to 40.0mm.
Resistant to solvents & chemicals
Highly temperature rated

Specifications: BS 2848

Sizes mm	Sizes inches	Sizes mm	Sizes inches
1.0 x 2.0	0.039 x 0.079	5.0 x 8.0	0.197 x 0.315
1.0 x 2.5	0.039 x 0.098	5.5 x 8.0	0.217 x 0.315
1.0 x 3.0	0.039 x 0.118	6.0 x 7.0	0.236 x 0.276
1.0 x 6.0	0.039 x 0.236	6.0 x 8.0	0.236 x 0.315
2.0 x 3.0	0.078 x 0.118	6.0 x 9.0	0.236 x 0.354
2.0 x 4.0	0.078 x 0.158	7.0 x 10.0	0.276 x 0.394
2.0 x 5.0	0.078 x 0.197	8.0 x 9.0	0.315 x 0.354
2.0 x 6.0	0.078 x 0.236	8.0 x 10.0	0.315 x 0.394
2.5 x 4.0	0.098 x 0.158	8.0 x 12.0	0.315 x 0.472
3.0 x 4.0	0.118 x 0.158	9.0 x 10.0	0.354 x 0.394
3.0 x 4.5	0.118 x 0.177	9.0 x 12.0	0.354 x 0.472
3.0 x 5.0	0.118 x 0.197	10.0 x 11.0	0.394 x 0.433
3.0 x 6.0	0.118 x 0.236	10.0 x 12.0	0.394 x 0.472
3.5 x 5.5	0.138 x 0.217	12.0 x 14.0	0.472 x 0.551
4.0 x 5.0	0.158 x 0.197	12.0 x 15.0	0.472 x 0.591
4.0 x 5.5	0.158 x 0.217		
4.0 x 6.0	0.158 x 0.236		
5.0 x 6.0	0.197 x 0.236		
5.0 x 6.5	0.197 x 0.256		
5.0 x 7.0	0.197 x 0.276		

Ordering Information

Colours : Various

For ordering : Specify the code type, size, colours & quantities. (Example: MW 12 x 15-X-200M)

Other ID Dimensions : Quoted on request.