


# Thermal Memory Ltd

6 Dodd Croft  
Rochdale  
Lancashire OL16 4QX  
Great Britain

Website : [www.shrinkfit.co.uk](http://www.shrinkfit.co.uk) E-mail : [shrinkfit@gmail.com](mailto:shrinkfit@gmail.com)



PTFE is extremely stable at high temperatures & can be used continuously at **+260°C**. It is one of the few polymers that retains a measure of toughness & strength even at cryogenic temperatures & has been used safely in outer space at temperatures well below **-70°C**.

It is virtually inert to all chemicals, organic solvents do not attack or dissolve it and is extremely hydrophobic and sheds vapours almost totally

SW

## PTFE Standard wall tubing AWG 0 to 28

Operating Temperature  
-70°C to +260°C

Main features  
Standard wall tubing  
Resistant to solvents & chemicals  
High temperature rated

Specifications: BS 2848 Type6 / Class 250T

AWG	ID mm	ID inches	Wall thickness mm	ID inches	AWG	ID mm	ID inches	Wall thickness mm	ID inches
0	8.53	0.336	0.38	0.015	13	1.93	0.076	0.30	0.012
1	7.62	0.300	0.38	0.015	14	1.73	0.068	0.30	0.012
2	6.81	0.268	0.38	0.015	15	1.57	0.062	0.30	0.012
3	6.07	0.239	0.38	0.015	16	1.42	0.056	0.30	0.012
4	5.44	0.214	0.38	0.015	17	1.27	0.050	0.30	0.012
5	4.83	0.190	0.38	0.015	18	1.14	0.045	0.30	0.012
6	4.29	0.169	0.38	0.015	19	1.02	0.040	0.30	0.012
7	3.84	0.151	0.38	0.015	20	0.89	0.035	0.30	0.012
8	3.43	0.135	0.38	0.015	22	0.71	0.028	0.25	0.010
9	3.02	0.119	0.38	0.015	24	0.58	0.023	0.25	0.010
10	2.72	0.107	0.30	0.012	26	0.51	0.020	0.25	0.010
11	2.44	0.096	0.30	0.012	28	0.41	0.016	0.23	0.010
12	2.16	0.085	0.30	0.012					

### Ordering Information

Colours : Natural, other colours to order.

For ordering : Please specify the code type, colour, size & quantities. Example SW 10-X-200M